

List of material according to TP 62-061-16 Gland packing

TEMAPACK 1170

1. Technical characteristics

Construction	Square knitting cord	
Material	Ramie	
Impregnate	PTFE	
Lubricate	Mineral oil	

2. Physical-mechanical properties obligatory for delivery and acceptance

	,				
	Specific unit	Nominal value	Tested to standard		
Dimension of the cord	mm				
Tolerance of dimension	mm	see TP 62-061-16, tab. 2			

3. Other physical-mechanical properties

1 J			
		Specific unit	Nominal value
Min operating temperature		°C	- 30
Max operating temperature		°C	+ 180
Max operating pressure	Valve		60
	Piston pump	bar	50
	Centrifugal		35
	pump		33
Max	Piston pump		5
operating	Centrifugal	m.s ⁻¹	13
velocity	pump		13
Density		g.cm ⁻³	1,4
Chemical resistance		рН	2 – 12

4. Chemical resistance table

1: Offerfical registance table	
Good resistance	Medium resistance
Sea water	Organic and inorganic solvents
Cold and hot water	Abrasive media
Weak solvents	Medium acid
Air, gases	Drinking water
Paper industry	Colour and paint
Oil and grease	Thinning lye
Food industry	Organic bonding agent
Drinking water	Salty solvents
Outlet water	